



ELiXA 3V

## For your **High-Speed Applications** ELiXA goes Monochrome

### Key Features

- Sensor size: 3 x 4096 pixels - 10x10µm
- Multi-line sensor
- Row spacing of 2 pixels (center to center)
- Linerate of 54 kHz
- Enhanced sensitivity thanks to back side illumination
- Bi-directional scanning
- Camera Link interface (medium)
- Mechanics: 70 x 76 x 54 mm<sup>3</sup>
- Fully configurable by the user with CommCam software

### Applications

- Web inspection: wood, paper, metallurgy
- Surface inspection: wafer, DVD/CDROM, PCB, flat panel display
- OCR and barcode reading: document scanning, checks sorting, data archiving, postal sorting

The ELiXA 3V 4096 pixel camera is the ideal candidate for the most demanding of applications requiring high speed acquisition. Using e2v's unique technology, the CCD sensor features unmatched performance: line rate up to 54KHz, row spacing of two pixels center to center between the three lines and enhanced response with the back side illumination technology.

- Easy calibration (Automatic tap balance and flat field correction, line balance)
- Versatile implementation (trigger modes, output modes, bidirectional scanning)

Detailed Specifications

Sensor Characteristics		
Resolution	pixels	3 x 4096
Pixel Size (square)	µm	10 x 10
Spacing Between Rows	µm	20 (center to center)
Line Length	mm	41
Max Line Rate	kHz	54

Functionalities (Programmable via Control Interface)	
Gain up to 25.4 dB (0.035 dB Steps)	
Offset -4096 to +4096 LSB	
Line Balance Automatic or Manual	
Flat Field Correction automatic or manual	
Scan Direction Reverse and forward	
Synchronization Modes: free run, external trigger	
Output Format: - Medium Camera Link 4 channels 8/10/12 bits	
Regulatory CE, FCC and RoHS compliant	

Radiometric Performance		
Bit Depth	bits	8, 10 or 12
Spectral Range	nm	300 - 1100
Non-linearity	%	+/- 1
Responsivity LSB	nJ/cm <sup>2</sup>	546

Mechanical and Electrical Interface		
Size (w x h x l)	mm	70 x 76 x 54
Lens Mount		F, T2, M42 x 1
Sensor Alignment	µm	better than +/-100
Sensor Flatness	µm	better than +/-35
Power Supply	V	single 12 to 24
Power Dissipation	W	< 15
Operating Temperature	°C	0 to 65 (front face)
Storage Temperature	°C	-40 to 70

Overview of e2v Line Scan Camera Range

Commercial Name	M/C	Max Data Rate M Pixels/s	Interface	Resolution	Bit Depth
AVIIVA SM2	Monochrome	60	CL/LVDS	512 to 4096	up to 12 bits
AVIIVA SC2	Colour	60	CL/LVDS	4096	up to 12 bits
AVIIVA UM2	Monochrome	62	GigE	512 to 4096	up to 12 bits
AVIIVA UC2	Colour	62	GigE	4096	up to 12 bits
AVIIVA UM4	Monochrome	160	CL	8192	up to 12 bits
AVIIVA UM8	Monochrome	320	CL	12 288	up to 12 bits
ELiXA UC8	Colour	320	CL	4 x 4096	up to 12 bits
ELiXA 3V	Monochrome	320	CL	3 x 4096	up to 12 bits
ELiXA 4S	Monochrome	80	CL	4 x 4096	up to 12 bits



Sales offices

European regional sales offices

e2v ltd

106 Waterhouse Lane  
Chelmsford - Essex CM1 2QU  
England  
T+44 (0)1245 493 493  
F+44 (0)1245 492 492  
enquiries@e2v.com

e2v sas

16 Burospace  
91572 Bièvres Cedex  
France  
T+33 (0)1 60 19 55 00  
F+33 (0)1 60 19 55 29  
enquiries-fr@e2v.com

e2v gmbh

Industriestraße 29  
82194 Gröbenzell  
Germany  
T+49 (0)8142 410 570  
F+49 (0)8142 284 547  
enquiries-de@e2v.com

Americas

e2v inc

4 Westchester Plaza  
Elmsford - NY 10523-1482  
USA  
T+1 (914) 592 6050  
F+1 (914) 592 5148  
enquiries-na@e2v.com

Asia Pacific

e2v ltd

11/F, Onfem Tower  
29 Wyndham Street, Central  
Hong Kong  
T+852 3679 364 8/9  
F+852 3583 1084  
enquiries-ap@e2v.com

Product Contact

e2v

Avenue de Rochepleine - BP 123  
38521 Saint-Egrève Cedex  
France  
T+33 (0)4 76 58 30 00  
F+33 (0)4 76 58 34 80  
hotline-cam@e2v.com

